



Electric Heating Unit

HOTBOY Multi 21 und 36 kW

Artikelnr. Kauf: HM2000000004 - 21 kW | HM2000000005 - 36 kW



Your advantages

- Incl. 3-way connector
- 3 heating programs for the drying of screed
- No waste gas emissions


The indispensable tool for innovative HVAC specialists. Small, flexible and suitable for any purpose. All components such as pumps, expansion vessel, controls, etc. are fully integrated and their use

meets all requirements, from drying of screed, to replacement of boilers, to temporary measures when heating systems or the DHW supply fail.




Technical specifications / Accessories

Type HOTBOY Multi	21 kW	36 kW
Heat output	21.6 kW	36 kW
Screed surface area	150 m ²	250 m ²
Power connection (3-way connector)	1N~230 V 16 A 3N~400 V 16 A 3N~400 V 32 A	3N~400 V 16 A 3N~400 V 32 A 3N~400 V 63 A
Upstream fuse	1 x 16 3 x 16 3 x 32 A	3 x 16 3 x 32 3 x 63 A
Max. power	2,4 7,2 21,6 kW	9 18 36 kW
Number of power levels	1 x 2,4 kW 3 x 2,4 kW 9 x 2,4 kW	1 x 9 kW 2 x 9 kW 4 x 9 kW
Weight	55 kg	65 kg
Dimensions (L x W x H)	650 x 550 x 1,150 mm	
Efficiency rating	99 %	
Protection class	IP 44	
Max. operating pressure	2.6 bar	
Min. operating pressure	0.4 bar	
Safety pressure	3.0 bar	
Temperature range	10 – 85 °C	
Safety temperature limiter	98 °C	
Expansion tank	8 Liter	
Boiler volume	11 Liter	
Connection	3/4" - GEKA	
Circulation pump	Wilo-Para Msl/6-43/Sc.	

Areas of application:



Subject to technical changes - only for information

Accessories	Item number
 HOTAIR MLE 20 Transportable air heaters up to 20 kW	HM2000000238
 HOFLOW MST 30 Mobile system separator up to 30 kW	HM2000000241
 HOT THERM MWS Hygienic hot water tank made of stainless steel	HM2000000258